



SAFETY DATA SHEET

XTEND LIQUID HIGH-N 34-0-0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name XTEND LIQUID HIGH-N 34-0-0
Product number LQF016,LQF017

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fertiliser for use on managed amenity turf

1.3. Details of the supplier of the safety data sheet

Supplier Headland Amenity Ltd
 1 Burr Elm Court
 Main Street
 Caldecote
 Cambridge
 Cambridgeshire
 CB23 7NU
 Tel. +44 (0)1223 491090
 sds.enquiries@headlandamenity.com

Contact person Wendy Windscheffel

1.4. Emergency telephone number

Emergency telephone +44 (0)1223 491090 (9.00 - 5.00 GMT Mon-Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
Health hazards Eye Irrit. 2 - H319
Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/attention.

XTEND LIQUID HIGH-N 34-0-0

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

AMMONIUM NITRATE (SOLUFEED)			50-70%
CAS number: 6484-52-2	EC number: 229-347-8	REACH registration number: 01-2119490981-27-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)		
Ox. Sol. 3 - H272 Eye Irrit. 2 - H319	O; R8. Xi; R36		
N-METHYL-2-PYRROLIDONE			<1%
CAS number: 872-50-4	EC number: 212-828-1	REACH registration number: 01-2119472430-46-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)		
Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 1B - H360D STOT SE 3 - H335 STOT SE 3 - H335 STOT SE 3 - H335	Xi; R36/37/38. Repr. Cat. 1 R61		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Remove affected person from source of contamination. Take off immediately all contaminated clothing and wash it before reuse. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	There may be irritation of the throat with a feeling of tightness in the chest.
Ingestion	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.
Skin contact	Skin contact may cause redness and irritation.
Eye contact	Irritation and redness, followed by blurred vision. Pain. Profuse watering of the eyes. May cause permanent damage.

XTEND LIQUID HIGH-N 34-0-0

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding environment.

Unsuitable extinguishing media No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Contain and absorb spillage with sand, earth or other non-combustible material. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Avoid spilling. Avoid contact with skin and eyes. Wash hands thoroughly after handling.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

XTEND LIQUID HIGH-N 34-0-0

8.1. Control parameters

Occupational exposure limits

N-METHYL-2-PYRROLIDONE

Long-term exposure limit (8-hour TWA): WEL 10 ppm 40 mg/m³

Short-term exposure limit (15-minute): WEL 20 ppm 80 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through skin.

N-METHYL-2-PYRROLIDONE (CAS: 872-50-4)

PNEC

- Fresh water; 0.25 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Ensure there is sufficient ventilation of the area.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Provide eyewash station.

Hand protection

Wear protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. Do not eat, drink or smoke when using this product.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Blue.
Odour	No characteristic odour.
Odour threshold	No information available.
pH	pH (concentrated solution): ~ 6.2
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	Mixture not classed as flammable
Evaporation rate	No information available.
Evaporation factor	No information available.

XTEND LIQUID HIGH-N 34-0-0

Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	No information available.
Bulk density	No information available.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product. Stable under normal conditions.

10.2. Chemical stability

Stability Stable at normal ambient temperatures. Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat.

10.5. Incompatible materials

Materials to avoid Strong acids. Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products In combustion emits toxic fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Inhalation There may be irritation of the throat with a feeling of tightness in the chest.

XTEND LIQUID HIGH-N 34-0-0

Ingestion	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.
Skin contact	There may be irritation and redness at the site of contact.
Eye contact	There may be irritation and redness. Profuse watering of the eyes. Pain. The vision may become blurred. May cause permanent damage.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential This product is not considered to bioaccumulate.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

XTEND LIQUID HIGH-N 34-0-0

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Supplier contact and emergency contact details updated.
Revision date	07/09/2015
Revision	2
Supersedes date	02/07/2015
Risk phrases in full	R8 Contact with combustible material may cause fire. R36 Irritating to eyes. R36/37/38 Irritating to eyes, respiratory system and skin. R61 May cause harm to the unborn child.
Hazard statements in full	H272 May intensify fire; oxidiser. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H360D May damage the unborn child.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.